

PRODUCT SPECIFICATIONS

MODEL No.	DESCRIPTION:		
2600	12GA Launching Cartridge	12GA Launching Cartridge	
		Revision E 5/21	



NOT TO SCALE

WARNING: CSI manufactures a variety of CTS less lethal products which are under pressure, pyrotechnic, incendiary, emit projectiles, generate smoke, or are explosive in nature. When used in accordance with CTS training guidelines and the individual agency's policy, they are intended to cause varying degrees of pain and injury, which are temporary. These products are restricted to law enforcement, corrections, and military personnel and are used to gain compliance, disperse crowds, restore order, or temporarily incapacitate dangerous persons. In rare circumstances, if used incorrectly, CTS less-lethal products may cause damage to property, serious bodily injury or death. Therefore, any person using the force option depicted on this page should receive proper training to ensure the safest and most effective use.

PHYSICAL & OPERATIONAL			
Туре	Launching Cartridge		
Caliber	12GA Shotgun		
Weapon Compatibility*	See Note		
Effective Range**	See Note		
Cartridge Length	1.6" (40.64 mm)		
Overall Weight	11.5 gm		

All specifications are average and are subject to change without notice.

All performance specifications are based on testing conducted in Jamestown, PA USA,
At an elevation of 1,058 feet above sea level at ambient temperature conditions.

SHIPPING INFORMATION		
Proper Shipping Name	Cartridges for Weapons, Blank	
UN Number	0014	
Hazard Class	1.4S	
Labels Required	Explosive 1.4S	
Quantity Per Package	400 Per Box	
Total Package Weight	20lbs.	
Package Type	Fiberboard Box	
Package Dimensions	17x11x 6	

*The Model 2600 Launching Cartridge is very short, 1.6". Therefore, to prevent weapon malfunctions, each cartridge must be manually loaded into the chamber for each shot.

**Effective range is dependent on the launching cup, launcher, and weight of munitions being launched. The baseline for performance of a Model 2600 Launching Cartridge is that it will launch a Model 9230 CS Grenade a minimum of 100 yards (91M); and a 9590 Sting-Ball Grenade a minimum of 65 yards (59M) from a LC9 Launching Cup on a Remington 870 shotgun, with cylinder bore and 18" bbl.

CAUTION: To prevent damage to the shotgun, when launching grenades, it is recommended to shoulder fire as opposed to putting the butt stock on the ground.









CTS is a Division of Combined Systems, Inc.

388 Kinsman Rd.
Jamestown, PA 16134 USA
TEL (724) 932-2177
FAX (724) 932-2166

EMAIL Sales@combinedsystems.com www.combinedsystems.com