


## PRODUCT SPECIFICATIONS

MODEL No.	DESCRIPTION:	
3213	37MM Multi 3, Smoke	
3223	37MM CN Multi 3	
3233	37MM CS Multi 3	
		Revision E 5/21



NOT TO SCALE

WARNING: CSI manufactures a variety of CTS less lethal products which are under pressure, pyrotechnic, incendiary, emit projectiles, generate smoke, or are explosive in nature. When used in accordance with CTS training guidelines and the individual agency's policy, they are intended to cause varying degrees of pain and injury, which are temporary. These products are restricted to law enforcement, corrections, and military personnel and are used to gain compliance, disperse crowds, restore order, or temporarily incapacitate dangerous persons. In rare circumstances, if used incorrectly, CTS less-lethal products may cause damage to property, serious bodily injury or death. Therefore, any person using the force option depicted on this page should receive proper training to ensure the safest and most effective use.

PHYSICAL & OPERATIONAL		
Туре	Irritant & Smoke Pyrotechnic Projectiles	
Caliber *	37MM / 40MM	
Weapon Compatibility	37MM 1.5" Riot Guns / M79 Type Grenade Launcher	
Cartridge Length	4.9" (124.4 mm)	
Effective Range**	80 yards (73 m)	
Overall Weight	205 gm	
Discharge Time	20-40 seconds	
Warranty	5 Years from Shipment Date	

All specifications are average and are subject to change without notice.

All performance specifications are based on testing conducted in Jamestown, PA USA,
At an elevation of 1,058 feet above sea level at ambient temperature conditions.

SHIPPING INFORMATION		
Proper Shipping Name	Ammunition Smoke	
UN Number	0303	
Hazard Class	1.4G	
Labels Required	Explosive 1.4G	
Quantity Per Package	96 Cartridges	
Total Package Weight	55 lb.	
Package Type	UN Specification 1A2/Y36/S Metal Drum with Lever Lock Lid	
Package Dimensions	19x12 (7 gal. drum )	

\*These muzzle munitions are designed with a "dual-rim" enabling the operator to chamber the round in both 37MM and 40MM Launchers. However, only 37MM will deliver optimum performance as stated in this specification sheet.









<sup>\*\*</sup>Effective range is dependent upon environmental factors, especially wind.